

# Specifications

		<b>XM1</b>	<b>XM1 S4 SUPPRESSOR</b>	<b>RX40</b>	<b>RX20 S3 SUPPRESSOR</b>	<b>RX20 SPORT</b>	<b>RX20 DYNAMIC</b>	<b>RX5</b>	<b>XP4</b>	<b>ATAC TS2</b>	<b>ATAC T2</b>	<b>X3TAC</b>	<b>X50</b>
<b>Stock</b>	Hardwood			•	•	•	•	•					•
	Black Synthetic	•	•	•	•	•	•	•	•	•	•	•	•
	Green Synthetic				•	•	•	•	•	•	•		
	Grey Synthetic				•	•	•	•					
<b>Caliber</b>	4,5 mm /.177 - 5,5 mm /.22	•	•	4,5 mm /.177	•	•	•	•	4,5 mm /.177	•	•	4,5 mm /.177	•
<b>Dimensions</b>	Total Length	39 in.	45 in.	43 in.	44 in.	44 in.	42 1/2 in.	41 in.	9.7 in.	43 in.	43 in.	35.4 in.	50 in.
		986 mm	1.146 mm	1.090 mm	1.122 mm	1.122 mm	1.080 mm	1.030 mm	246 mm	1.080 mm	1.080 mm	900 mm	1.270 mm
	Barrel Length	22 in.	28 1/2 in.	16 1/2 in.	14 in.	18 in.	16 1/2 in.	16 1/2 in.	6.7 in.	16 1/2 in.	16 1/2 in.	14.5 in.	19 1/4 in.
		565 mm	725 mm	420 mm	366,7 mm	461,8 mm	419,7 mm	420 mm	170 mm	420 mm	420 mm	370 mm	490 mm
<b>Weight</b>	2,5 Kg without scope	2,6 Kg without scope	3 Kg without scope	3 Kg without scope	3 Kg without scope	3 Kg without scope	2,4 Kg without scope	1.2 Kg	3.2 Kg	3.2 Kg	2.1 Kg	4.1 Kg	
<b>Safety</b>	Automatic	•	•	•	•	•	•	•	•	•	•	•	•
<b>Optics</b>	4x32	•	•		•	•	•	•					
	3-9x40 A0			•						•	•		•
<b>Trigger</b>	Factory set - double stage							•				•	
	Adjustable - double stage			•	•	•	•			•	•		•
	Adjustable Sliding Trigger System	•	•										
<b>Velocity</b>	Caliber 4,5 mm	320 m/s	320 m/s	305 m/s	305 m/s	305 m/s	305 m/s	200 m/s	110 m/s	305 m/s	305 m/s	140 m/s	360 m/s
	Caliber 5,5 mm	274 m/s	274 m/s		240 m/s	240 m/s	240 m/s	150 m/s		240 m/s	240 m/s		280 m/s