

# Specifications



		XM1	XM1 S4 SUPPRESSOR	RX20TAC RX20TAC S2 SUPPRESSOR	RX40	RX20 S3 SUPPRESSOR	RX20 SPORT	RX20 DYNAMIC	RX5	XP4	ATAC TS2	ATAC T2	X3TAC	X50
<b>Stock</b>	Hardwood				•	•	•	•	•				•	•
	Black Synthetic	•	•	•	•	•	•	•	•	•	•	•	•	•
	Green Synthetic									•	•	•		
<b>Caliber</b>	4,5 mm /.177 - 5,5 mm /.22	•	•	•	4,5 mm /.177	•	•	•	•	4,5 mm /.177	•	•	4,5 mm /.177	•
<b>Dimensions</b>	Total Length	39 in.	45 in.	44 in.	43 in.	44 in.	44 in.	42 1/2 in.	41 in.	9.7 in.	43 in.	43 in.	35.4 in.	50 in.
		986 mm	1.146 mm	1.122 mm	1.090 mm	1.122 mm	1.122 mm	1.080 mm	1.030 mm	246 mm	1.080 mm	1.080 mm	900 mm	1.270 mm
	Barrel Length	22 in.	28 1/2 in.	18 in.	16 1/2 in.	14 in.	18 in.	16 1/2 in.	16 1/2 in.	6.7 in.	16 1/2 in.	16 1/2 in.	14.5 in.	19 1/4 in.
565 mm		725 mm	461,8 mm	420 mm	366,7 mm	461,8 mm	419,7 mm	420 mm	170 mm	420 mm	420 mm	370 mm	490 mm	
<b>Weight</b>		2,5 Kg without scope	2,6 Kg without scope	3 Kg without scope	3 Kg without scope	3 Kg without scope	3 Kg without scope	3 Kg without scope	2,4 Kg without scope	1.2 Kg	3.2 Kg	3.2 Kg	2.1 Kg	4.1 Kg
<b>Safety</b>	Automatic	•	•	•	•	•	•	•	•	•	•	•	•	•
<b>Optics</b>	4x32	•	•			•	•	•	•					
	3-9x40 AO			•	•						•	•		•
<b>Trigger</b>	Factory set - double stage								•				•	
	Adjustable - double stage			•	•	•	•	•			•	•		•
	Adjustable Sliding Trigger System	•	•											
<b>Velocity</b>	Caliber 4,5 mm	320 m/s	320 m/s	305 m/s	305 m/s	305 m/s	305 m/s	305 m/s	200 m/s	110 m/s	305 m/s	305 m/s	140 m/s	360 m/s
	Caliber 5,5 mm	274 m/s	274 m/s	240 m/s		240 m/s	240 m/s	240 m/s	150 m/s		240 m/s	240 m/s		280 m/s